



5.01

BLUE PLICORD® EXTREMEFLEX™



Product Specifications

APPLICATION: A high-tech, flexible corrugated hose with pretzel-like agility and proven performance. Best of all, it's available at a non-corrugated price, making it a great value. With ExtremeFlex, there's even more to appreciate:

- > Flexible Handling: Easier to move in and out of tight spaces and around sharp corners.
- > Lightweight: Easier to lift and carry, so there are fewer workplace injuries.
- > Lower Force to Bend: Easier to connect and disconnect, keeping productivity high.

CONSTRUCTION TUBE: White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A Sanitary Standard 18-03).

COVER: Blue Chemivic™ corrugated synthetic rubber (wrapped impression).

REINFORCEMENT: Spiral-plied synthetic fabric with galvanized wire helix.

TEMPERATURE: - 32°C to 100°C

BRANDING (SPIRAL): Continental ContiTech® Plicord® ExtremeFlex® Food Grade 150 PSI WP.

NON-STOCK/SIZES: For special production run minimum requirements, please contact customer service.

PLANT CODES: 549-462 (white)
549-164 (gray)
549-212 (blue)

BLUE PLICORD® EXTREMEFLEX™

PRODUCT NO.	ID		NOM. OD		MAX. WP		BEND RADIUS		VACUUM HG		WEIGHT		ROLL LENGTH
	in.	mm.	in.	mm.	psi	Mpa	in.	mm.	in.	mm.	lb/ft.	kg/m.	m.
20019284	3/4	19	1.2	30.5	150	1.03	2	50	29	737	0.47	0.70	30.48
20818640	1	25	1.4	36.8	150	1.03	1	25	29	737	0.59	0.88	30.48
20818642	1¼	32	1.7	42.2	150	1.03	1¼	32	29	737	0.63	0.94	30.48
20818645	1½	38.1	1.9	49.3	150	1.03	1½	38	29	737	0.77	1.15	30.48
20818648	2	51.2	2.4	62.0	150	1.03	2	51	29	737	1.00	1.48	30.48
20818664	2½	63.7	3.0	77.5	150	1.03	2½	63	29	737	1.61	2.38	30.48
20818666	3	76.1	3.5	89.9	150	1.03	3	76	29	737	1.89	2.79	30.48
20818667	4	102.1	4.6	116.6	150	1.03	4	102	29	737	2.69	3.98	30.48

^F or Continental ContiTech® food compliance information, see Appendix C. ^F 3/4 hose supplied as White flexwing.

Insta-lock food fittings available; BSM and Tri Clover.

Melbourne • Sydney • Adelaide

1300 767 035

sales@mhsgroup.com.au
hosesolutions.com.au